

RÉFÉRENCES

- Anonymous 1964. Steady flow of groundwater towards wells. Proc. Comm. Hydrol. Research TNO No.10, 179 p.
- Barenblatt, G.E., Zheltov, I.P. and Kochiona, I.N. 1960. Basic concepts in the theory of homogeneous liquids in fractured rocks. Jnl Appl. Math. Mech., **24**(5): 1286-1303.
- Bear, J. and Jacobs, M. 1965. On the movement of water bodies injected into aquifers. Journal of Hydrology, **3**: 37-57.
- Bierschenk, W.H. 1963. Determining well efficiency by multiple step-drawdown tests. Intern. Assoc. of Sci. Hydrol. Publ.64, pp.493-507.
- Boersma, L. 1965. Field measurement of hydraulic conductivity below a water table. In Methods of Soil Analysis, Part 1, C.A. Black Editor, Agronomy No.9, pp.222-233. American Society of Agronomy, Madison, Wisconsin.
- Boulton, N.S. 1954. Unsteady radial flow to a pumped well allowing for delayed yield from storage. Intern. Assoc. Sci. Hydrol., Rome, Publ.37, pp.472-477.
- Boulton, N.S. 1963. Analysis of data for non-equilibrium pumping tests allowing for delayed yield from storage. Proceedings of the Institute of Civil Engineers, **26**: 469-482.
- Boulton, N.S. and Streltsova, T.D. 1976. The drawdown near an abstraction well of large diameter under non-steady conditions in an unconfined aquifer. Journal of Hydrology, **30**: 29-46.
- Boulton, N.S. and Streltsova, T.D. 1977. Unsteady flow to a pumped well in a fissured water bearing formation. Journal of Hydrology, **35**: 257-270.
- Bouwer, H. 1989. Bouwer and Rice slug test - an update. Ground Water, **27**: 304-309.
- Bouwer, H. and R.D. Jackson, 1974. Determining soil properties. Drainage for Agriculture, ed. J. van Schilfhaarde, Am. Soc. of Agronomy, Madison, Wis., pp.611-672.
- Brikowski, T. 1993. Flow between aquifers through filled cylindrical conduits: analytical solution and application to underground nuclear testing sites. Journal of Hydrology, **146**: 115-130.
- Brillant, J. 1966. La mesure *in situ* des perméabilités locales. Géotechnique, **3**(1): 33-52.
- Bouwer, H. and R.C. Rice. 1976. A slug test for determining hydraulic conductivity of unconfined aquifers with completely or partially penetrating wells. Water Resources Research, **12**(3): 423-428.
- Bureau of Reclamation. 1977. Ground Water Manual. U.S. Dept. of the Interior. Superintendent of Documents, U.S. Govt. Printing Office, Washington, D.C.
- Butler, J.J. 1990. The role of pumping tests in site characterization: some theoretical considerations. Ground Water, **28**(3): 394-402.
- Butler J.J. and Hyder, Z. 1994. An assessment of the Nguyen and Pinder method for slug tests analysis. Ground Water Monitoring and Remediation, **14**(4): 124-131.
- Cambefort, H. 1965. Curiosités des massifs alluvionnaires et des nappes d'eau. Annales de l'Institut Technique du Bâtiment et des Travaux Publics, **211-212**: 921-947.
- CAN/BNQ 2501-130-M88, 1988. Soils - Determination of permeability at the end of a casing. National Standard of Canada.

- CAN/BNQ 2501-135-M88, 1988. Soils - Determination of permeability by the Lefranc method. National Standard of Canada.
- Castany, G. 1982. *Principes et méthodes de l'hydrogéologie*. Dunod Université, Paris.
- Chapuis, R.P. 1987. Piézomètres hydrauliques et risques d'erreur associés. National Research Council Canada, ACGR Technical Memorandum **143**: 117-145.
- Chapuis, R.P. 1988. Determining whether wells and piezometers give water levels or piezometric levels. *In* Ground Water Contamination: Field Methods, ASTM **STP 963**: 162-171.
- Chapuis, R.P. 1989. Shape-factors for permeability tests in boreholes and piezometers. *Ground Water*, **27**(5): 647-654.
- Chapuis, R.P. 1992a. «Estimation of storativity from recovery data»: Discussion. *Ground Water*, **30**(2): 269-272.
- Chapuis, R.P. 1992b. Using Cooper-Jacob approximation to take account of pumping well pipe storage effects in early drawdown data of a confined aquifer. *Ground Water*, **30**(3): 331-337.
- Chapuis, R.P. 1994a. Assessment of methods and conditions to locate boundaries: I. One or two straight impervious boundaries. *Ground Water*, **32**(4): 576-582.
- Chapuis, R.P. 1994b. Assessment of methods and conditions to locate boundaries: II. One straight recharge boundary. *Ground Water* **32**(4): 583-590.
- Chapuis, R.P. 1998. Overdamped slug test in monitoring wells: Review of interpretation methods with mathematical, physical and numerical analysis of storativity influence. *Canadian Geotechnical Journal*, **35**(5): 697-719.
- Chapuis, R.P. and Chenaf, D. 1995. Pelican River aquifer test: Solving the divergences in T and S for observation well E1. Proceedings, Solutions'95, 26th IAH International Congress, Edmonton, pp.CHA1-6.
- Chapuis, R.P. and Chenaf, D. 1998. Detecting a hydraulic short-circuit along a monitoring well with the recovery curve of a pumping test in a confined aquifer: method and example. *Canadian Geotechnical Journal*, **35**(5): 790-800.
- Chapuis, R.P., and Sabourin, L. 1989. Effects of installation of piezometers and wells on groundwater characteristics and measurements. *Canadian Geotechnical Journal*, **26**(4): 604-613.
- Chapuis, R.P. and Wendling, G. 1991. Monitoring wells: measurement of permeability with minimal modification of groundwater. *Canadian Journal of Civil Engineering*, **18**(5): 871-875.
- Chapuis, R.P., Crespo, R., Chenaf, D., and Aubertin, M. 1993. Evaluation of a ground water f.e.m. software for steady and unsteady state conditions. Proceedings, 46th Canadian Geotechnical Conference, Saskatoon, pp.61-70.
- Chapuis, R.P., Soulié, M., and Sayegh, G. 1990. Laboratory modelling of field permeability tests in cased boreholes. *Canadian Geotechnical Journal*, **27**(5): 647-658.
- Chapuis, R.P., Gill, D.E. et Wendling, G. 1987. Comparaisons des valeurs de conductivité hydraulique obtenues soit par essais de pompage soit par essais de laboratoire. Proc. 40th Canadian Geotechnical Conf., Regina, pp.291-300.
- Chapuis, R.P., J.J Paré, and J.G. Lavallée. 1981. In situ variable head permeability tests. Proceedings, Xth International Conference on Soil Mechanics and Foundation Engineering, Stockholm, Vol.1, pp.401-406.

- Chenaf, D. and Chapuis, R.P. 1995. Contribution to the analysis of aquifer tests in both pumping and recovery phases for the case of recharge boundary conditions. Proceedings, Solutions'95, 26th IAH International Congress, Edmonton, pp.CHE1-CHE6.
- Cooper, H.H. Jr., and Jacob, C.E. 1946. A generalized graphical method for evaluating formation constants and summarizing well-field history. Transactions, American Geophysical Union, **27**(4): 526-534.
- Cooper H.H. Jr., J.D. Bredehoeft and I.S. Papadopoulos. 1967. Response of a finite-diameter well to an instantaneous change of water. *Water Resources Research*, **3**(1): 263-269.
- Craun, G.F. 1981. Outbreaks of waterborne disease in the United States: 1971-1978. *Journal of the American Water Works Association*, **73**(7): 360-369.
- Daviau, F. 1986. *Interprétation des essais de puits - Les méthodes nouvelles*. Éditions Technip. Paris.
- De Glee, G.J. 1930. *Over grondwaterstromingen bij wateronttrekking door middel van putten*. Thesis. J. Waltman, Delft, The Netherlands, 175 p.
- De Glee, G.J. 1951. *Berekeningsmethoden voor de winning van groundwater*. In *Drinkwatervoorziening, 3e Vacantiecursus: 38-80 Moorman's periodieke pers.*, The Hague.
- Dorsey, N.E. 1968. *Properties of ordinary water substance*. Hafner Publishing Company, New York.
- Driscoll, F.G. 1986. *Groundwater and Wells*. 2nd Edition, Johnson Division, St. Paul, Minnesota, 1108 p.
- EPA. 1993. *Subsurface characterization and monitoring techniques: A desk reference guide*. Volume 1: Solids and groundwater, Appendices A and B. EPA/625R-93/003a, Office of Research and Development, Washington DC.
- Euler, L. 1748. *Introductio in Analysisio Infinitorum*. Berlin.
- Faust, C.R. and J.W. Mercer. 1984. Evaluation of slug tests in wells containing a finite-thickness skin. *Water Resources Research*, **20**(4): 504-506.
- Ferrandon, 1948. Les lois de l'écoulement de filtration. *Le Génie Civil*, **125**(2): 24-28.
- Ferris, J.G., Knowles, D.B., Brown, R.H. and Stallman, R.W. 1962. *Theory of aquifer tests*. U.S. Geological Survey Water-Supply Paper 1536-E, 69-174.
- Ferris, J.G. 1949. *Ground Water*. In *Hydrology*, Wisler, C.O. and Brater, E.F., Editors. John Wiley & Sons, New York.
- Freeze, R.A. and Cherry, J.A. 1979. *Groundwater*. Prentice-Hall, 604p.
- Gambolati, G. 1976. Transient free surface flow to a well: An analysis of theoretical solutions. *Water Resources Research*, **12**: 27-39.
- Genetier, B. 1984. *La pratique des pompages d'essai en hydrogéologie*. Manuels et méthodes, Éditions du BRGM, Orléans, France.
- Gibson, R.E., 1966. A note on the constant head test to measure soil permeability in situ. *Géotechnique*, **16**(3): 256-257.

- Gibson, R.E., 1970. An extension to the theory of the constant head *in situ* permeability test. *Géotechnique*, **20**(2): 193-197.
- Glaisher, J.W.L. 1870. Tables of the numerical values of the sine-integral, cosine-integral and exponential-integral. *Philos. Trans. Royal Society London*, **160**: 367-388.
- Gringarten, A.C. 1978. A study by the finite-element method of the influence of fractures in confined aquifers. *Jnal of the Society of Petroleum Engs*, 183.
- Gringarten, A.C. 1984. Interpreting tests in fissured and multilayered reservoirs with double porosity behavior: theory and practice. *Jnal of the Society of Petroleum Engs*, 584.
- Hantush, M.S. 1956. Analysis of data from pumping tests in leaky aquifers. *Transactions, American Geophysical Union*, **37**: 702-714.
- Hantush, M.S. 1959. Analysis of data from pumping wells near a river. *Journal of Geophysical Research*, **94**: 1921-1932.
- Hantush, M.S. 1960. Modification of the theory of leaky aquifers. *Journal of Geophysical Research*, **65**: 3713-3725.
- Hantush, M.S. 1961a. Drawdown around a partially penetrating well. *ASCE Journal of the Hydraulic Division*, **87**(HY4): 83-98.
- Hantush, M.S. 1961b. Aquifer tests on partially penetrating wells. *ASCE Journal of the Hydraulic Division*, **87**(HY5): 171-195.
- Hantush, M.S. 1962. Flow of ground water in sands of nonuniform thickness; 3. Flow to wells. *Journal of Geophysical Research*, **67**: 1527-1534.
- Hantush, M.S. 1964. *Hydraulics of wells*. In *Advances in Hydrosience*, vol.1, Ven Te Chow Editor, Academic Press, New York, pp.281-432.
- Hantush, M.S. and Jacob, C.E. 1955. Non-steady radial flow in an infinite leaky aquifer. *Transactions American Geophysical Union*, **36**: 95-100.
- Huisman, L. 1972. *Groundwater recovery*. MacMillan, New York.
- Hvorslev, M.J. 1951. Time-lag and soil permeability in ground water observations. *Bulletin 36*, U.S. Army Engineering Waterways Experimental Station, Vicksburg, Miss.
- Jacob, C.E. 1944. Notes on determining permeability by pumping tests under water table conditions. U.S. geological Survey, Open File Report.
- Jacob, C.E. 1947. Drawdown test to determine effective radius of artesian well. *Transactions ASCE*, **112**: 1047-1064.
- Jacob, C.E. 1963. The recovery method for determining the coefficient of transmissibility. In *Methods of Determining Permeability, Transmissibility and Drawdown*. U.S. Geological Survey Water-Supply Paper 1536-I, pp.281-292.
- Kabala, Z.J., F. Pinder, and P.C.D. Milly. 1985. Analysis of well-aquifer response to a slug test. *Water Resources Research*, **21**(9): 1433-1436.
- Kazemi, H. 1969. Pressure transient analysis of naturally fractured reservoirs with uniform fracture distribution. *Jnal of the Society of Petroleum Engs*, 246.
- Keys, W.S. 1988. Borehole geophysics applied to ground-water investigations. U.S. Geological Survey Open-File Report 87-539, 305 p.

- Kipp, K.L. Jr. 1985. Type curve analysis of inertial effects in the response of a well to a slug test. *Water Resources Research*, **21**(9): 1397-1408.
- Knowles, D.B. 1955. Ground water hydraulics: a summary of lectures presented by J.G. Ferris. U.S. Geological Survey Open-File Report.
- Kruseman, G.P. and De Ridder, N.A. 1991. Analysis and evaluation of pumping test data. International Institute for Land Reclamation and Improvement, Pub. 47, Wageningen, The Netherlands.
- Lefranc, E. 1936. Procédé de mesure de la perméabilité des sols dans les nappes aquifères et application au calcul du débit des puits. *Le Génie Civil*, **CIX**(15): 306-308.
- Lefranc, E. 1937. La théorie des poches absorbantes et son application à la détermination du coefficient de perméabilité en place et au calcul du débit des nappes d'eau. *Le Génie Civil*, **CXI**(20): 409-413.
- Lohman, S.V. 1972. Ground Water Hydraulics. U.S. Geological Survey Professional Paper 708, 70p.
- Luthin, J.N. and Don Kirkham. 1949. A piezometer method for measuring permeability of soil *in situ* below a water table. *Soil Science*, vol. 5T.68, pp.349-358.
- Mabillot, A. 1971. Les forages d'eau - Guide pratique. Technique & Documentation, Paris, 237p.
- Mandel, J. 1939. Note sur le calcul des infiltrations. *Annales des Ponts et Chaussées*, Juillet, pp.57-110.
- MEF, 1995. Les périmètres de protection autour des ouvrages de captage des eaux souterraines. Ministère de l'environnement et de la faune, Éditeur officiel du Québec.
- Mieussens, C. and Ducasse, P. 1977. Mesure en place des coefficients de perméabilité et des coefficients de consolidation horizontaux et verticaux. *Canadian Geotechnical Journal*, **14**(1): 76-90.
- Miller, R.T. 1981. Hydrologic data for the Pelican River sand-plain aquifer, Western Minnesota. US Geological Survey Open-File Report 80-695, St.Paul, Minnesota.
- Moench, A.F. 1984. Double-porosity models for a fissured groundwater reservoir with fracture skin. *Water Resources Research*, **20**: 831-846.
- Moench, A.F., P.A. Hsieh, C.R. Faust, and J.W. Mercer. 1985. Evaluation of slug tests in wells containing a finite-thickness skin; discussion and reply. *Water Resources Research*, **21**(9): 1459-1462.
- Navfac DM7, 1974. Design Manual - Soil Mechanics, Foundations, and Earth Structures. U.S. Government Printing Office, Washington, D.C.
- Neuman, S.P. 1972. Theory of flow in unconfined aquifers considering delayed response of the water table. *Water Resources Research*, **8**: 1031-1045.
- Neuman, S.P. 1973. Supplementary comments on «Theory of flow in unconfined aquifers considering delayed response of the water table». *Water Resources Research*, **9**: 1102-1103.
- Neuman, S.P. 1979. Perspective on «Delayed yield». *Water Resources Research*, **15**: 899-908.
- Neuman, S.P. 1990. Universal scaling of hydraulic conductivities and dispersivity in geologic media. *Water Resources Research*, **26**: 1149-1158.

- Neuman, S.P. and Witherspoon, P.A. 1972. Field determination of hydraulic properties of leaky multiple aquifer systems. *Water Resources Research*, **8**: 1284-1298.
- Nguyen, V. and Pinder, G.F. 1984. Direct calculation of aquifer parameters in slug test analysis. *In* Groundwater Hydraulics, J. Rosensheim and G.D. Bennett Editors, American Geophysical Union, Water Resources Monograph 9, pp.222-239.
- Nind, T.E.W. 1965. Influences of absolute and partial hydrologic barriers on pump test results, *Canadian Journal of Earth Sciences*, **2**: 309-323.
- Papadopoulos, S.S. and Cooper H.H. Jr. 1967. Drawdown in a well of large diameter. *Water Resources Research*, **1**: 241-244.
- Papadopoulos, I.S., J.D. Bredehoeft and H.H. Cooper. 1973. On the analysis of slug test data. *Water Resources Research*, **9**(4): 1087-1089.
- Raghunath, H.M. 1982. *Ground Water*. Wiley Eastern Limited, New Delhi.
- Ramey, H.J. 1982. Well-loss function and the skin effect: a review. *In* Recent Trends in Hydrogeology. Narasimhan, T.N. Editor. Geological Society of America, Special Paper 189, pp.265-271.
- Rat, M., F. Laviron and J.C. Jorez. 1970. Essai Lefranc. *Bulletin de Liaison des Laboratoires Routiers*, No. Spécial N, pp.56-66.
- Rat, M. and F. Laviron. 1974. Mesures du coefficient de perméabilité par essais ponctuels. *Bulletin de Liaison des Laboratoires des Ponts et Chaussées*, pp.179-182.
- Rorabaugh, M.J. 1953. Graphical and theoretical analysis of step-drawdown test of artesian aquifer. *ASCE Proceedings*, Vol.79, Separate No.362, 23p.
- Rouleau, A., Denis, C., Cousineau, P. et Lapcevic, P. 1996. The estimation of hydraulic parameters of a fractured orthoquartzite formation at the laboratory and field scales. *Proceedings, 2nd North Am. Rock Mech. Symp., Montréal*, Vol.2, pp.1359-1366.
- Rushton, K.R. and Howard, K.W.F. 1982. The unreliability of open observation boreholes in unconfined aquifer pumping tests. *Ground Water*, **20**: 546-550.
- Sakthivadivel, R. and Rushton, K.R. 1989. Numerical analysis of large diameter wells with a seepage face. *Journal of Hydrology*, **107**: 43-55.
- Schneebeli, G. 1954. Mesure *in situ* de la perméabilité d'un terrain. *Comptes-rendus des 3e Journées d'Hydraulique*, Alger, pp.270-279.
- Schneebeli, G. 1956. Sur l'hydraulique des puits. *Symposia Darcy*, Publication No.41 de l'A.I.H., tome 2, pp.10-27.
- Schneebeli, G. 1966. *Hydraulique souterraine*. Eyrolles, Paris, 362p.
- Schoeller, H. 1962. *Les eaux souterraines*. Masson, Paris.
- Sen, Z. 1990. Numerical analysis of large diameter wells with a seepage face - Comment. *Journal of Hydrology*, **119**: 393-398.
- Silliman, S. and Higgins, D. 1990. An analytical solution for steady-state flow between aquifers through an open well. *Ground water*, **28**: 184-190.
- Spaine, F.A. Jr. and Wurstner, S.K. 1993. DERIV: A computer program for calculating pressure derivatives for use in hydraulic test analysis. *Ground Water*, **31**(5): 814-822.

- Stallman, R.W. 1963. Type curves for the solution of single boundary problems. Shortcuts and special problems in aquifer tests, compiled by R. Bentall, U.S. Geological Survey paper 1545-C, 45-47.
- Streltsova, T.D. 1972a. Unconfined aquifer and slow drainage. *Journal of Hydrology*, **16**: 117-124.
- Streltsova, T.D. 1972b. Unsteady radial flow in an unconfined aquifer. *Water Resources Research*, **8**: 1059-1066.
- Streltsova, T.D. 1973. On the leakage assumption applied to equations of groundwater flow. *Journal of Hydrology*, **20**: 237-253.
- Streltsova, T.D. 1976. Progress in research on well hydraulics. *Advances in groundwater hydrology*. Amer. Water Resources Assoc., pp.15-28.
- Taylor, D.W. 1948. *Fundamentals of soil mechanics*. Chapman & Hall, London, p.194.
- Theis, C.V. 1935. The relation between the lowering of the piezometric surface and the rate and duration of discharge of a well using groundwater storage. *Transactions, American Geophysical Union*, **16**: 519-524.
- Thiem, G. 1906. *Hydrologische Methoden*. Gebhardt, Leipzig, 56p.
- Todd, D.K. 1980. *Groundwater hydrology*. 2nd Ed. John Wiley & Sons, New York, N.Y.
- Van der Kamp, G. 1985. Brief quantitative guidelines for the design and analysis of pumping tests. In *Hydrology in the Service of Man*. Mem. 18th Congress IAH, Cambridge, pp.197-206.
- Vibert, A. 1954. Sur une démonstration des formules de Dupuit. *Le Génie Civil*.
- Vonhof, J.A. 1975. Hydrodynamic response - or slug test as a means to monitor the progress of well development. *Canadian Geotechnical Journal*, **12**(1): 1-12.
- Walton, C.J. 1962. *Groundwater resource evaluation*. McGraw-Hill, New York.
- Warren, J.E. and Root, P.J. 1963. Behavior of naturally fractured reservoirs. *Journal of the Society of Petroleum Engineers*, **228**: 245-255.
- Wilkinson, W.B. 1968. Constant head *in situ* permeability tests in clay strata. *Géotechnique*, **18**(2): 172-194.
- Williams, J.H., and Conger, R.W. 1990. Preliminary delineation of contaminated water-bearing fractures intersected by open-hole bedrock wells. *Ground Water Monitoring Review*, **10**(4): 118-126.